
































ATLAS 0 TRACK COMPONENTS

Quantity		Description/Number
40		10-inch straight (6050)
2		4.5-inch straight (6051)
2		1.75-inch straight (6052)
3		5.5-inch straight (6053)
2		40-inch straight (6058)
3		uncoupling track (6059)
22		cut-to-length straight
2		0-36 30-degree curve (6066)
2		0-36 custom-cut curve
6		0-54 22.5-degree curve (6060)
1		0-54 11.25-degree curve (6061)
2		0-54 custom-cut curve
31		0-72 22.5-degree curve (6062)
2		0-72 11.25-degree curve (6063)
3		0-72 custom-cut curve
5		0-81 22.5-degree curve (6011)
13		0-99 22.5-degree curve (6014)
5		0-99 custom-cut curve (6014)
2		0-90 22.5-degree curve (6013)
1		custom-radius curve
1		0-45 left-hand turnout (6085)
1		0-54 left-hand turnout (6070)
1		0-72 left-hand turnout (6072)
1		0-72 custom-cut left-hand turnout
7		0-72 right-hand turnout (6073)
1		0-72 'Y' track switch, 11.25-degree (6074)
2		0-72/0-54 left-hand turnout (6077)
2		0-72/0-54 right-hand turnout (6078)
2		no. 5 left-hand turnout (6024)
1		no. 5 right-hand turnout (6025)
2		45-degree crossing (6082)
6		snap-on bumper (6040)